



# SAFETY JOGGER

## INDUSTRIAL



Medium

## BESTRUN S3

### Breathable Steel Toe Work Shoes

Designed for automotive, mining, and oil work, Safety Jogger BESTRUN safety shoes provide steel protection, S3 slip resistance, and breathable comfort.

|               |                                                                     |
|---------------|---------------------------------------------------------------------|
| Upper         | Barton Action Leather                                               |
| Lining        | Recycled Mesh                                                       |
| Footbed       | SJ foam footbed                                                     |
| Midsole       | Steel                                                               |
| Outsole       | PU/PU                                                               |
| Toecap        | Steel                                                               |
| Category      | S3 / SR, SC, LG, FO, CI                                             |
| Size range    | EU 35-48 / UK 3.0-13.0 / US 3.0-13.5<br>JPN 21.5-31.5 / KOR 230-315 |
| Sample weight | 0.665 kg                                                            |
| Norms         | ASTM F2413:2018<br>EN ISO 20345:2022+A1:2024                        |



BLK




**S3**  
S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



**Steel toecap**  
Robust metal support to protect the feet of the wearer against falling or rolling objects.



**Steel midsole**  
Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



**Oil & fuel resistant**  
The outsole is resistant against oil and fuel.



**Breathable leather upper**  
Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



**SRC slip resistance**  
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.

SAFETY  
JOGGER  
WORKS

HEAD-TO-TOE  
PROTECTION

ENGINEERED  
IN EUROPE

[www.safetyjogger.com](http://www.safetyjogger.com)

**Industries:**  
Automotive, Chemical, Cleaning, Construction, Logistics, Mining, Oil & Gas, Industry

**Environments:**  
Dry environment, Muddy environment, Uneven surfaces, Wet environment

**Maintenance instructions:**  
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

|         | Description                                                      | Measure unit          | Result      | EN ISO 20345 |
|---------|------------------------------------------------------------------|-----------------------|-------------|--------------|
| Upper   | <b>Barton Action Leather</b>                                     |                       |             |              |
|         | Upper: permeability to water vapor                               | mg/cm <sup>2</sup> /h | 2.2         | ≥ 0.8        |
|         | Upper: water vapor coefficient                                   | mg/cm <sup>2</sup>    | 25          | ≥ 15         |
| Lining  | <b>Recycled Mesh</b>                                             |                       |             |              |
|         | Lining: permeability to water vapor                              | mg/cm <sup>2</sup> /h | 49.8        | ≥ 2          |
|         | Lining: water vapor coefficient                                  | mg/cm <sup>2</sup>    | 398.8       | ≥ 20         |
| Footbed | <b>SJ foam footbed</b>                                           |                       |             |              |
|         | Footbed: abrasion resistance (dry/wet) (cycles)                  | cycles                | 25600/12800 | 25600/12800  |
| Outsole | <b>PU/PU</b>                                                     |                       |             |              |
|         | Outsole abrasion resistance (volume loss)                        | mm <sup>3</sup>       | 56.4        | ≤ 150        |
|         | Basic Slip resistance - Ceramic + NaLS - Forward heel slip       | friction              | 0.44        | ≥ 0.31       |
|         | Basic Slip resistance - Ceramic + NaLS - Backward forepart slip  | friction              | 0.41        | ≥ 0.36       |
|         | SR Slip resistance - Ceramic + glycerin - Forward heel slip      | friction              | 0.29        | ≥ 0.19       |
|         | SR Slip resistance - Ceramic + glycerin - Backward forepart slip | friction              | 0.29        | ≥ 0.22       |
|         | Antistatic value                                                 | MegaOhm               | 120.7       | 0.1 - 1000   |
|         | ESD value                                                        | MegaOhm               | N/A         | 0.1 - 100    |
|         | Heel energy absorption                                           | J                     | 29          | ≥ 20         |
| Toecap  | <b>Steel</b>                                                     |                       |             |              |
|         | Impact resistance toecap (clearance after impact 100J)           | mm                    | N/A         | N/A          |
|         | Compression resistance toecap (clearance after compression 10kN) | mm                    | N/A         | N/A          |
|         | Impact resistance toecap (clearance after impact 200J)           | mm                    | 15          | ≥ 14         |
|         | Compression resistance toecap (clearance after compression 15kN) | mm                    | 15          | ≥ 14         |

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



HEAD-TO-TOE  
PROTECTION

